


got caulking?

CHOICE OF PROFESSIONALS



WWW.COLORRITEINC.COM

Birmingham, AL

Decatur, AL



Mobile, AL

Montgomery, AL

- Easy Application
- Water Clean-up
- Moisture Resistant
- Mildew Resistant



Matching your world with an exact color match

Use what the professionals use.
Over 450 colors in stock now!!



Siliconized Acrylic Caulk
Exact Color Matched For Your Project



100% Particulated RTV Silicone Sealant
For Granite, Quartz, Solid Surface, & much more...

Discover the Possibilities

Poly-Sil gives you an inconspicuous look every time with over 100 varieties available.

- Granite
- Quartz Surfaces
- Laminates
- Solid Surfaces
- Stone
- Concrete Countertops
- Tile
- Engineered Stone

Silicone with an ATTITUDE

Now offered in 3 finishes!
-Standard, Satin & Sanded

Available in over 300 colors

- Tile & Grout Applications
- Bathroom Fixtures
- Countertops
- And More...



100% RTV Silicone Sealant
Watertight Seal/Excellent Adhesion

"THE ONE STOP CAULK SHOP"

color RITE
INCORPORATED™

SEE REVERSE SIDE FOR ADDITIONAL INFORMATION



Manufacturers of Exact Color Matched Sealants



100% RTV Silicone Sealant Sanded or Unsanded

Color Rite Sealant / Adhesive Caulk is especially formulated for today's demands of the professional installer / fabricator. Color Rite dries firm but flexible enough to work in a variety of applications.

COLOR MATCHED TO

- Athletic Flooring
- Bamboo Flooring
- Cabinetry
- Engineered Stone
- Granite
- Kitchen/Bath Fixtures
- Laminate Wood Flooring
- Laminates
- Linoleum Flooring
- Marble
- Paints and Coatings
- Quartz
- Rubber/Vinyl Wall Base
- Solid Plank Wood Flooring
- Solid Surfaces
- Stains
- Stair Treads
- Stucco/EFIS
- Tile/Grouts
- Vinyl Flooring
- Wall Coverings



Coverage: 1/8" x 1/8" 55 linear feet
Coverage measured using 5.5 fl. oz. Tube.

Coverage: 3/16" x 3/16" 55 linear feet
Coverage measured using 10.5 fl. oz. Cartridge.

Poly-Sil is a 100% RTV Silicone Sealant. Poly-Sil utilizes a broad spectrum of colored particulates to achieve color coordination with the granular appearing patterns of granite, quartz, solid surface, textured products and laminates, for the kitchen and bath industries. Poly-Sil having excellent adhesion, flexibility and moisture resistance makes Poly-Sil the choice for professionals needing 100% RTV Silicone Sealant.

COLOR MATCHED TO

- Concrete Countertops
- Cultured Marble
- Engineered Stone
- FRP/FRL Panels
- Granite
- Kitchen/Bath Fixtures
- Laminates
- Marble
- Quartz
- Solid Surfaces
- Tile/Grouts
- And More...



Coverage: 1/8" x 1/8" 57.8 linear feet



The Perfect Tool for the Perfect Bead



Color Sil is a 100% RTV Silicone Sealant. Formulated to perform a wide variety of applications. Color Sil has excellent adhesion to surfaces such as: solid surface, cultured marble, quartz, granite, plumbing fixtures, baths, showers, tile/grout applications, and wood/laminate flooring as a perimeter sealant. Other uses: doors, windows, gutters, siding, vents, flashing, glass and more. Excellent around the home as well as in commercial applications.

COLOR SIL APPLICATIONS

- Brick/Masonry
- Concrete Countertops
- Cultured Marble
- Engineered Stone
- Exterior Moldings
- FRP/FRL Panels
- Glass
- Granite
- Kitchen/Bath Fixtures
- Laminates
- Marble
- Melamine Panels
- Metal Extrusions
- Paper Based Products
- Quartz
- Siding
- Solid Surfaces
- Stucco/EFIS
- Tile/Grouts
- Windows & Doors



Coverage: 1/8" x 1/8" 90 linear feet

- Acclimate:**
Time (48 hours) for materials to adjust to a new environment.
- Blushing:**
Condensation of moisture on a surface that occurs when solvent evaporates from contact adhesive.
- Canister:**
Self-contained adhesive spray system.
- Closed Time:**
Interval between the point when a PVA composite is put together and when it is pressed.
- Cold Pressing:**
A hydraulic or screw press in which the glued members are forced together.
- Coverage:**
Amount of adhesive that is applied - measured in wet mils for PVA and g/ft² for contacts.
- Coverage Rate:**
The bonded amount of material that can be produced at a recommended adhesive coverage.
- Dead Stack:**
Pressure being applied to a laminated panel by only the weight of the core. No mechanical pressure is applied.
- Density:**
Mass per unit volume.
- Dry Time:**
The period of time during which an adhesive needs to dry prior to bonding.
- Flatwork:**
Also known as non-postforming.
- Freeze-Thaw Stable:**
A system able to freeze and thaw without losing chemical or physical properties.
- Glue Spreader:**
A piece of equipment with grooved rollers capable of applying adhesive in wet mils.
- Green Strength:**
Initial strength of adhesives that prevents laminate from springing back until it cures to full strength.
- Heat Strength:**
Strength measured at elevated temperature.
- Homogenized:**
Product will not separate, no need for agitation.
- Hot Press:**
A single or multi-platen hydraulic press, with plates or platens, heated by steam, for thermo-setting resin adhesives.
- Joint Assembly:**
The junction of two adjacent pieces of wood or veneer.
- J-Rolling:**
A manual method for applying pressure to a bonded assembly.
- Open Time:**
This is the window of time that begins when an adhesive is applied to the substrate and ends when the laminate is applied to make an assembly. Temperature and humidity affect open time.
- Pinch Roller:**
A mechanized roller which applies precise and continuous pressure over the entire panel.
- Postforming:**
Postforming describes the process of bending laminate around curves with the application of heat (approximately 325°F). A postforming adhesive has the ability to hold the laminate to the curved substrate while still at postforming temperatures.
- Postforming, High-Speed:**
This type of application uses highly automated equipment to postform at high line speeds.
- Press Time:**
The time which the assembly to be bonded remains under the pressure necessary for bonding.
- Solids Content:**
The percentage by weight of nonvolatile material in an adhesive or sealant.
- Spray Pot:**
A pressurized system which uses compressed air to atomize and spray the adhesive. The compressed air is supplied by a compressor.
- Strength:**
The adhesive's bonding power that resists force, strain or wear.
- Substrate:**
The basic surface upon which the adhesive is applied and to which it is expected to adhere.
- Tack:**
The property of an adhesive that enables it to form a bond of measurable strength immediately after adhesive and adherent are brought into contact under low pressure.
- VHAP (Volatile Hazardous Air Pollutant):**
A hazardous air pollutant is one of over 180 specific chemicals identified by the US Government as being detrimental to air quality.
- Viscosity:**
The resistance of a fluid to flow.
- VOC (Volatile Organic Compounds):**
Carbon-containing chemicals which contribute to the formation of ground level ozone (smog).

Visit us on the web at www.unitedplywoods.com

Birmingham, AL
1640 Mims Ave. SW
Ph: 205-925-7601
Fax: 205-925-1315
800-272-6486

Decatur, AL
723 Old Trinity Road
Ph: 256-355-3161
Fax: 256-355-0073
800-321-6886



Mobile, AL
5445 Business Parkway
Ph: 251-378-0188
Fax: 251-378-0190
877-531-7468

Montgomery, AL
581 Trade Center Street
Ph: 334-265-6721
Fax: 334-265-6725
800-392-8024

WILSONART ADHESIVES

CONTACT ADHESIVE BRUSH/ROLLER GRADES

WA600



A consumer grade, flammable brush/roller grade contact adhesive with easy application and more forgiving drying characteristics. High solids. Sold individually.

Item #	Size	Qty/Box
45160	Quart	12
45162	1 Gallon	6
45164	5 Gallon	N/A

CONTACT ADHESIVE Waterborne - WA H2O



Polychloroprene adhesive for postforming operations using brush, roller or spray application. Less than 20g/L VOC. Nonflammable.

Contact your local branch for more information.



CONTACT ADHESIVE

740A



Aerosol spray for laminating in the shop and/or on the job-site. High strength and high heat resistant. Methylene chloride free. Natural color. 12 per box. Sold individually.

Item #	Description
45239	740A – 14.2-oz



WOOD GLUE - WHITE Quick-Setting



For use with hard and soft woods. Provides hard glue line with good durability and bonding strength. Sets in 4 to 6 minutes. 4 per box. Sold individually.

Item #	Color	Size Gal.
45622	White	1

WILSONART ADHESIVES

WOOD GLUE - WHITE

WA10



Fast setting PVA adhesive designed for wood-to-wood applications and panel manufacturing operations requiring faster machine times. Dries clear. Greenguard certified. 4-Gallons per box. Sold individually.

Item #	Size
45010	1-Gallon

WOOD GLUE - YELLOW



For assembly and cold press applications. Non-toxic, non-flammable fast setting wood adhesive. Resistant to heat and solvents. Pint = 12 per box. Gallon = 4 per box. Sold individually.

Item #	Description
45024	1-Pint
45026	1-Gallon

ADHESIVES & CAULKING

Visit us on the web at www.unitedplywoods.com

Birmingham, AL
1640 Mims Ave. SW
Ph: 205-925-7601
Fax: 205-925-1315
800-272-6486

Decatur, AL
723 Old Trinity Road
Ph: 256-355-3161
Fax: 256-355-0073
800-321-6886



Mobile, AL
5445 Business Parkway
Ph: 251-378-0188
Fax: 251-378-0190
877-531-7468

Montgomery, AL
581 Trade Center Street
Ph: 334-265-6721
Fax: 334-265-6725
800-392-8024

WILSONART ADHESIVES

WOOD GLUE - YELLOW
WA30



A high strength, fast-setting, yellow PVA adhesive designed for wood-to-wood applications. Ideal for assembly, cold press and hot press applications. Fluorescent dye added for easier clean up. Greenguard certified. Sold individually.

Item #	Size
45027	5-Gallon

WOOD GLUE - TYPE II



A water-resistant PVA assembly adhesive. WA Type II can be used in hot or cold press panel operations, or in radio frequency curing operations. Type II water resistance. Greenguard certified. 4-Gallons per box. Sold individually.

Item #	Size
45210	1-Gallon

MELAMINE ADHESIVE

WA M



Premium acrylic adhesive. Can be used to bond non-porous materials (including: melamine, vinyl, high pressure laminate, PVC, wood veneer, metal, stone, tile and acrylics) to wood and composite surfaces. 4-Gallons per box. Sold individually

Item #	Size
45205	1-Gallon

PVA ADHESIVES

WA3100



A PVA adhesive designed specifically to bond laminate to a variety of substrates in cold press applications. High strength, fast setting, easy clean up. Greenguard certified. Sold by the drum.

Item #	Color	Size
45202	White	55-Gallon

Jowat
Adhesives

EDGEBANDING ADHESIVES

Hot Melt



Cartridges & pellets for use on solid wood, veneer, PVC and paper edgelanding. Can also be used for precoating and soft forming applications. Ethylene vinyl acetate (EVA) formula provides good wetting and adhesion. Application temperature 374°F to 410°F. Cartridges: 48 pcs per box. Sold in full box qty's.

Pellets: 44 lbs per bag. Sold by the bag.

Item #	Description	Color
45610	Cartridges	Natural
45603	Pellets	Natural



SILICONE SEALANTS

Axiom 25™



100% translucent silicone. For use with all solid surface products, marble, engineered stone and other nonporous surfaces. Ideal for fastening and sealing back splashes, window sills and tub/shower surrounds. Also for creating hygiene seals in refrigeration and food preparation applications. Fast-curing. Resists UV exposure, ozone, moisture and mildew. Can be dispensed in temperatures from -35°F to 160°F. Packaged in 10.3 oz. cartridge. 12 per box. Sold individually.

Item #	Color
89890	Blue
89891	Charcoal
89892	Green
89894	Gray
89895	Beige
89898	White

Visit us on the web at www.unitedplywoods.com

Birmingham, AL
1640 Mims Ave. SW
Ph: 205-925-7601
Fax: 205-925-1315
800-272-6486

Decatur, AL
723 Old Trinity Road
Ph: 256-355-3161
Fax: 256-355-0073
800-321-6886



Mobile, AL
5445 Business Parkway
Ph: 251-378-0188
Fax: 251-378-0190
877-531-7468

Montgomery, AL
581 Trade Center Street
Ph: 334-265-6721
Fax: 334-265-6725
800-392-8024

NUDO
Products, Inc.

FRP ADHESIVE
Fiber-Lite®



Item #	Description
62020	4 Gal. FRP adhesive

WILSONART ADHESIVES

ADHESIVE CLEANER
WA121



Designed to dissolve/remove dried adhesive overspray, residue from fabricated parts and decorative surfaces. Extremely flammable. Gallons = 4 per box. Sold individually.

Item #	Size
45109	1-Gallon
45110	5-Gallon

"We are"



"Brands"

UNITED GLUE BOTTLE



Sold individually.

Item #	Description
BOTTLE	16 Oz.



GLUE BOTTLE - GLUBOT™



The Glubot™ is designed with a 2-chamber system that pushes glue from the bottom up through the secondary side chamber which ensures fresh glue every time. When you stop squeezing, the Glubot™ sucks the glue back inside and leaves a clean, clog free tip. Can be used with wood glue, paint thinner, lacquer thinner, alcohol and water. Comes with straight glue line guide, blade and yorker style tips. Sold individually.

Item #	Description
GB-GLUBOT	16 oz. Glue Bottle

GLUE ROLLERS & ROLLER FRAME



9" Roller cover, 9" roller frame & disposable 3" roller with handle. Apply solvent-based and water-based adhesives, paints and varnishes quickly with these products. Sold individually.

Item #	Description
RC-9T	9" Textured Roller Cover
RF-9	9" Roller Frame
RD-3	3" Disposable Roller w/Handle

ADHESIVES & CAULKING

Visit us on the web at www.unitedplywoods.com

Birmingham, AL
1640 Mims Ave. SW
Ph: 205-925-7601
Fax: 205-925-1315
800-272-6486

Decatur, AL
723 Old Trinity Road
Ph: 256-355-3161
Fax: 256-355-0073
800-321-6886



Mobile, AL
5445 Business Parkway
Ph: 251-378-0188
Fax: 251-378-0190
877-531-7468

Montgomery, AL
581 Trade Center Street
Ph: 334-265-6721
Fax: 334-265-6725
800-392-8024

