



POWER VENTILATOR 2000 CFM



Aluminum construction. Features 5 balanced fan blades and 8x8 aluminum screen attached for insect protection. Deep drawn flange and rain shield to keep water out. Factory-set adjustable thermostat : switches on at 100 degrees and off at 85 degrees. 3.4 Amps, 1-HP, 1,100 RPM, 120-Volts. Baseplate dimensions: 20" x 23".

Item #	Color
2000BL	Black
2000BR	Brown
2000WB	Weathered Bronze

REPLACEMENT POWER VENT MOTOR



Sold individually.

Item #	Description
2000MOT	Motor For 2000 Power Vent

ROOF LOUVER 700 Series



Aluminum rust-free construction. Features three sides louvered for greater air flow, large nailing flange, weather-tight sealed collar. Fits all pitched roofs. Prevents roof discoloration. Bird-proof. CSA-approved. Overall size: 16" x 20-5/16" x 5".

Item #	Color
750BL	Black
750BR	Brown

ROOF LOUVERS



Used for weather protection. 8x8 aluminum screen attached. Provides 144 Sq. inches of net free area. Overall size: 20" x 23" x 7-3/4".

Item #	Color
135BL	Black
135BR	Brown

WHIRLYBIRD TURBINE VENTS



Internally braced. Sold individually.

Item #	Color	Turbine Hole Size In.	Turbine Height In.	Turbine Base In.
BIB-12BL	Black	12	17-1/4	20x20
BIB-12BR	Brown	12	17-1/4	20x20
BIB-12ML	Mill	12	17-1/4	20x20
BIB-12WB	Weathered Bronze	12	17-1/4	20x20
BIB-14BL	Black	14	20	22x22
BIB-14BR	Brown	14	20	22x22
BIB-14ML	Mill	14	20	22x22
BIB-14WB	Weathered Bronze	14	20	22x22

Visit us on the web at www.unitedplywoods.com

Birmingham, AL
1640 Mims Ave. SW
Ph: 205-925-7601
Fax: 205-925-1315
800-272-6486

Decatur, AL
723 Old Trinity Road
Ph: 256-355-3161
Fax: 256-355-0073
800-321-6886




Mobile, AL
5445 Business Parkway
Ph: 251-378-0188
Fax: 251-378-0190
877-531-7468

Montgomery, AL
581 Trade Center Street
Ph: 334-265-6721
Fax: 334-265-6725
800-392-8024



RIDGE VENT
OmniRidge



Features internal aerodynamic curved baffles, external perpendicular omni baffles, weatherproof under-lapping joint, four drain holes per foot per side, external venturi baffle, 10 supported nail holes, molded nail lines, alignment tabs, external water shield, slot width guide lines and patented molded fanfold end plugs. Adjust from 2/12 to 16/12 roof pitches. Sold in carton quantities.

Item #	Section Length Ft.	Net Free Area In.2	Number Per Carton
OR-4	4	72	10 Sections or 40 ft.

SHINGLE OVER RIDGE VENTS



Features compact 30 foot roll, exterior convolute baffles, patented molded fanfold end plugs, omni baffles, molded centerline and nail holes marked every 6 inches. Can be cut at one foot intervals. Adjusts from 2/12 to 16/12 roof pitches. Includes two coils of 1" nails.

Item #	Section Length Ft.	Net Free Area In.2	Number Per Carton
LOR-30	30	330	1 Roll or 30 ft.

POWERED CRAWLSPACE VENT



Features 110 Cfm ball bearing motor, humidity sensor and thermostat shuts fan off at low temperatures. Helps stop mold growth. Mounts behind foundation vent for invisible operation. U.L. approved. 6 Pcs per carton.

Item #	Size In.	Description	Cubic Feet Louver Ventilates
PCV1	9 x 19 x 3	Polypropylene Plastic Powered Crawlspace Vent	1,650

LOW-PROFILE RIDGE VENT



Features 3/8"x1/2" slotted weep holes in wind baffles for water run-off, 1/8"x1" louvered openings inverted to block weather infiltration, pre-notched nail holes for installation, large 2" wide nailing flange. Adjustable from 3/12 to 12/12 roof pitches. Can be cut to desired length at 2-foot intervals. Tight-fitting high-density polyethylene foam end plug available.

Item #	Color	Section Length Ft.	Net Free Area In.2	Number Per Carton
LPR-10BL	Black	10	180	10 Sections or 100 ft.

LOW-PROFILE RIDGE VENT
L-Plug



Tight-fitting high-density polyethylene foam.

Item #	Pieces Per Box
L-Plug	24

Visit us on the web at www.unitedplywoods.com

Birmingham, AL
1640 Mims Ave. SW
Ph: 205-925-7601
Fax: 205-925-1315
800-272-6486

Decatur, AL
723 Old Trinity Road
Ph: 256-355-3161
Fax: 256-355-0073
800-321-6886



Mobile, AL
5445 Business Parkway
Ph: 251-378-0188
Fax: 251-378-0190
877-531-7468

Montgomery, AL
581 Trade Center Street
Ph: 334-265-6721
Fax: 334-265-6725
800-392-8024